


Amberg Clearance GRP 5000 Profiler 5033



The configuration consists of

- Premium hardware GRP 5000
- Application specific software Clearance Plus
- Robust and guaranteed precision thanks to GRP Fidelity
- First-class application support

Technical data GRP 5000

System configuration		Cont. system accuracy	
Gauge (mm)	1000, 1067, 1435, 1520/24, 1600, 1668/76	Profile accuracy - relative to track axis - at a distance of 5 m	+/- 5 mm
Profiling unit	Amberg Profiler 5033	Object point accuracy*)	+/- 2 - 4 cm
Compatible	Leica HDS6000/ 6100/7000 Z+F Imager 5006/5010	- GRP with total station	
*) For more details, see „GRP 5000 - System specification and typical accuracies for system application“.			
Profiler 5033 / 5033		Positioning	
Scanner type	Infrared phase shift	Leica total stations - motorised, ATR - radio modem	TS15/16, TS30, TS50/60, MS50/60
Range (Ambiguity interval)	5033 187.3 m	Leica GPS	GPS1200, GS10/14/15/16/18
Sensor performance		Power supply	
Profile surveying (Lateral offset and height to track axis)		GRP system	GBC 5000 battery, rechargeable > 5 h
Max. data acquisition rate - Pixels/sec	1'000'000	Battery life*)	> 5 h
Amberg Profiler Max. scan speed - Rotations/sec	50	Panasonic control computer Battery life*)	Li-Ion battery, rechargeable > 4 h
Track geometry measurement (Position, Gauge, Superelevation)		*) Depending on conditions.	
Kinematic measurement - data frequency	TPS: 7 Hz GPS: 10 Hz	Environmental specifications	
System accuracy		Lighting conditions	Darkness to daylight
Track coordinate*) - GRP with total station	+/- 5 mm	Working temperature range	-10° to +45° C
Superelevation	+/- 1.0 mm	Humidity	Non-condensing
Gauge	+/- 0.3 mm	System weight	
		GRP 5000 - ready to measure - incl. battery and computer	56 kg

System use and typical system performance

Clearance Plus applications		
Typical project applications	<ul style="list-style-type: none"> - Clearance surveying - Clearance gauging - Structure gauging - Compliance checks of lineside installations - Structure condition assessment 	
Typical project performance		
Application	Clearance surveying	Variant studies
Project section, lengths	1'000 m	1'000 m
Required point density	10 x 10 mm	20 x 20 mm
Surveying		
Typical measuring speed *) GRP with total station / **) GRP with GPS	1.8 km/h	1.0 km/h*) / 3.6 km/h**)
Track occupation	33 min	60 min *) / 17 min**)
Track geometry data	Stationing, Gauge, Superelevation	Stationing, Gauge, Superelevation, 3D track position
Analysis		
Working time interactive (operator) / automatic (PC)	1.5 h / 6 h	1.5 h / 6 h
Results		
	2D clearance map, cross-sections	3D point cloud cross-sections
System approval		
CE Conformity	EN 61326-1:2013 EN 61000-6-2:2005 EN 61000-6-4:2007/A1:2011 EN 60825-1:2014 EN 13977:2011 Directives 2014/30/EU Directives 2014/35/EU Directives 2011/65/EU	
GRP System FX approvals from	Network Rail / London Underground (UK), Deutsche Bahn (DE), SBB (CH), SNCF (FR), ÖBB (AT), RFI (IT), Adif (ES), ProRail (NL), Infrabel (BE)	
Extract of references		
Amberg's railway surveying solutions have proven their high performance all over the world. Demanding projects have been successfully realised in e.g. Germany, Austria, Belgium, the Netherlands, Denmark, France, Italy, Spain, Greece, Turkey, Australia, United Kingdom, Saudi Arabia, UAE, Korea, USA, PR China.		

Amberg Clearance GRP 5000 Profiler 5033

System performance and technical data

Amberg Clearance

Speedy and definite clearance assessments with real-time results. Modular system solution for automatic clearance surveying completed by typical railway analyses and documentation.

Project data management




- Central database for input, visualisation and management of clearance envelopes, clearance models, track project data including route data chronology, control points and measuring epochs.
- Flexible and user-friendly clearance envelope editor.
- Provision of all clearance specifications for subsequent surveying tasks and evaluations.

Surveying

- Profile measurements in 2D clearance mode or 3D coordinate mode with combined collection of all relevant track geometry data (stationing, gauge, superelevation, 3D track coordinates (with TPS, GPS only)).
- User-definable data registration mode depending on project requirements:
 - Continuous point cloud registration
 - Definable interval profile recording
 - Targeted individual profile surveying
- Comparison and display of profile distances between measured object and selected theoretical clearance envelope in real-time directly on site – including alarm function for clearance envelope violation.

Evaluation

- Fully automatic evaluation by comparing clearance surveys with a predefined clearance model for given section – either relative to the current track position or (for 3D data) in terms of a predefined, theoretical track position.
- Comprehensive, automatic reporting:
 - Traditional profile plot including clearance distances.
 - Extensive clearance mapping – stored with scaled image documentation for clear identification of potential encroachments.
 - 3D visualisation including colouring of all critical clearance objects and including an option for creating videos of the surveyed section.
-



Amberg Technologies AG
Trockenloostrasse 21
CH-8105 Regensdorf
Switzerland
Phone +41 44 870 92 22
info@amberg.ch
www.ambergtechnologies.ch

